

Pneumatic Test Program – Test (Orthopedic Seat Backrest)


Preliminary work:

PSE control module voltage supply 23 PSE ⇒ 1.0, 2.0
 PSE Control Module Test 32 PSE

Data (mbar)

Test Procedure	Permissible deviation
Allowable system leakage at 600 mbar pressure in 1 minute.	30 mbar

Special Tools



201 589 13 21 00

Tester

Pneumatic Test Program – Test (OSB)

A. Entire system

Preparation for Test:

1. Provide access to PSE control module (A37) and disconnect **grey** OSB pneumatic line with socket from PSE control module.
2. Connect tester to disconnected pneumatic line using connector 202 805 03 44.

Parts Required for Test:

- | | | |
|---|----------------------------|---------------|
| 1 | Connector | 202 805 03 44 |
| 2 | Pneumatic hose, 50 mm long | 007 997 61 82 |
| 1 | Pneumatic line, 1 m long | 000 158 14 35 |

Note:

The connections on the PSE control module and pneumatic multiple connector are marked with their German acronyms. In other words:
ZV (German) = **CL** (English),
SRU (German) = **MVA** (English),
OSL (German) = **OSB** (English).

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
1.0	Complete multi-contour backrest system Lower OSB center insert	Yellow connector on tester.	Set pressure adjuster for lower OSB center insert to maximum. Set pressure adjuster for upper OSB center insert and seat cushion length to minimum. Set side bolster rocker switch to minimum. Apply 600 mbar pressure in each of the 3 height settings.	Pressure loss 30 mbar in 1 minute.	32 PSE/OSB ⇒ 5.0, 32 PSE/OSB ⇒ 6.0, 32 PSE/OSB ⇒ 7.0, 32 PSE/OSB ⇒ 8.0, 32 PSE/OSB ⇒ 9.0

Pneumatic Test Program – Test (OSB)

A. Entire system

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
2.0	Complete multi-contour backrest system Upper OSB center insert	Yellow connector on tester.	Set pressure adjuster for upper insert to maximum. Set pressure adjuster for lower OSB center insert and seat cushion length to minimum. Set side bolster rocker switch to minimum. Apply 600 mbar pressure in each of the 3 height settings.	Pressure loss 30 mbar in 1 minute.	32 PSE/OSB ⇒ 5.0, 32 PSE/OSB ⇒ 6.0, 32 PSE/OSB ⇒ 7.0, 32 PSE/OSB ⇒ 8.0, 32 PSE/OSB ⇒ 9.0
3.0	Complete multi-contour backrest system Side bolster	Yellow connector on tester.	Set side bolster rocker switch to maximum. Set pressure adjuster for lower and upper OSB inserts and seat lengthen to minimum. Apply 600 mbar pressure in each of the 3 height settings.	Pressure loss 30 mbar in 1 minute.	32 PSE/OSB ⇒ 5.0, 32 PSE/OSB ⇒ 6.0, 32 PSE/OSB ⇒ 7.0, 32 PSE/OSB ⇒ 8.0, 32 PSE/OSB ⇒ 9.0

Pneumatic Test Program – Test (OSB)

A. Entire system

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
4.0	<p>Complete multi-contour backrest system Seat cushion length (models 129, 202, 208, 210 only)</p>	<p>Yellow connector on tester.</p>	<p>Set pressure adjuster for seat cushion lengthen to maximum. Set pressure adjuster for lower and upper OSB center insert to minimum. Set side bolster rocker switch to minimum. Apply 600 mbar pressure in each of the 3 height settings.</p>	<p>Pressure loss 30 mbar in 1 minute.</p>	<p>32 PSE/OSB ⇒ 5.0, 32 PSE/OSB ⇒ 6.0, 32 PSE/OSB ⇒ 7.0, 32 PSE/OSB ⇒ 8.0, 32 PSE/OSB ⇒ 9.0</p>

B. Line with pressure reservoir/line with control valve

Preparation for Test:

1. Connect tester to the **grey** OSB pneumatic line which leads to either the pressure reservoir below the rear seat cushion or to the control valve, using connector 202 805 03 44.

The disconnected pneumatic lines are to be reconnected to the distributor with connector 007 997 61 82.

Notes:

- When testing the pneumatic lines with the pressure reservoir, cap the pneumatic lines which lead to the control valves.
- When testing the pneumatic lines with control valves, disconnect the pneumatic line at pressure reservoir and cap using connector 124 805 02 44.

Parts Required for Test:

1	Connector, 50 mm long	007 997 61 82
1	Connector	202 805 03 44
1	Cap	000 987 11 45
2	Connector	124 805 02 44

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
5.0	Line and pressure reservoir	Yellow connector on tester.	Apply 600 mbar pressure to line and pressure reservoir.	Pressure drop 5 mbar in 1 minute.	Pressure reservoir leaks, Replace reservoir, 32 PSE/OSB ⇒ 8.0
6.0	Line and control valve	Yellow connector on tester.	Set pressure adjusters as well as rocker switch at control valve to minimum. Apply 600 mbar pressure to line and control valve.	Pressure drop 5 mbar in 1 minute.	32 PSE/OSB ⇒ 7.0, 32 PSE/OSB ⇒ 8.0

Pneumatic Test Program – Test (OSB)

C. Control valve

Preparation for Test:

1. Connect tester to separation connection underneath seat.

Parts Required for Test:

- | | | |
|---|--------------------------|---------------|
| 1 | connector | 202 805 03 44 |
| 2 | Rubber hose, 50 mm long | 007 997 61 82 |
| 1 | Pneumatic line, 1 m long | 000 158 14 35 |

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
7.0	OSB control valve, Multi-contour seat pressurized in each of the 3 height positions	Yellow connector on tester.	Set pressure adjusters and rocker switches to minimum. Apply 600 mbar pressure to pressure regulator.	Pressure drop 5 mbar in 1 minute.	Control valve or pneumatic line to control valve leaks. Replace.

Pneumatic Test Program – Test (OSB)

D. Lines

Preparation for Test:

1. Connect tester to one end of pneumatic line and plug other end with cap, part no. 000 987 11 45.

Parts Required for Test:

- | | | |
|---|-------------------------|---------------|
| 1 | Cap | 000 987 11 45 |
| 1 | Rubber hose, 50 mm long | 007 997 61 82 |
| 1 | Connector | 202 805 03 44 |
| 1 | Connector | 124 805 02 44 |

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
8.0	Leakage while pressurized	Yellow connector on tester.	Apply 600 mbar pressure to lines.	Pressure drop 0 mbar in 1 minute.	Pneumatic line with connectors leak. Replace.

Pneumatic Test Program – Test (OSB)

E. Air cushion

Preparation for Test:

1. Provide access to connector between control valve and pneumatic lines.

Parts Required for Test:

- | | | |
|---|--------------------------|---------------|
| 1 | Rubber hose, 50 mm long | 007 997 61 82 |
| 1 | Pneumatic line, 1 m long | 000 158 14 35 |

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
9.0	Air cushion and pneumatic line leakage in side bolster or seat cushion	Yellow connector on tester.	Apply 200 mbar pressure individually to each line in the pneumatic harness.	Pressure drop 5 mbar in 1 minute.	Air cushion and pneumatic line in side bolster or seat cushion leak. Replace.