





Electrical Test Program – Test

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
1.0	Electrolytic capacitor (C3) Function		Ignition: OFF Radio (A2): ON Tune radio to weak station in AM band. Engine: at idle	No change in the reception quality.	Electrolytic capacitor (C3) in right C-pillar.
2.0	High frequency wire to radio (A2) Short circuit (shielding/signal wire)		Radio (A2): OFF Disconnect connector from radio (A2) and FM/AM rear window antenna amplifier (A2/18) (Figure 1).	< 10 Ω ∞ Ω	Wiring.
3.0	Radio (A2) Control voltage	WO  A2/18 b	Disconnect connector from (A2/18) (Figure 1). Radio (A2): ON	11 – 14 V	Wiring, D.M., Information/Communication, Vol. 1, Radio (RD) – 3.1 23

Electrical Test Program – Test

⇒	Test scope	Test connection	Test condition	Nominal value	Possible cause/Remedy
4.0	FM/AM rear window antenna amplifier (A2/18)		Connect ammeter between A2/18 and automatic antenna control wire from radio (A2) (Figure 1). Radio (A2): ON	52 – 72 mA	A2/18, ⇒ 5.0, Values are OK: however, there is a poor reception quality: Replace A2/18 and retest using Function Test 11, If reception problem continues, replace rear window antenna.
5.0	Ground connection A2/18		Radio (A2): OFF Note: Do not loosen mount nuts for A2/18, since mount also functions as ground for A2/18.	< 1 Ω	Connection (mount) resistance at ground point.

Electrical Test Program – Test

Connection – Schematic




Figure 1

- A2/18 FM/AM rear window antenna amplifier
- WO Ground and mount point
- a High frequency connection wire to radio
- b Automatic antenna control wire from radio

P82.62-0238-57